

Advanced Instruments Inc.

Technical Specifications *

| Accuracy: | < 2% of FS range under constant conditions |
|----------------------|--|
| Analysis Ranges: | 0-10 PPM, 0-100 PPM, 0-1000 PPM, 0-1%, 0-25% (CAL) FS Auto-ranging or manual lock on a single range |
| Application: | Oxygen analysis down to 0.1 PPM in inert, helium, hydrogen, mixed and acid (CO_2) gas streams |
| Area Classification: | General purpose |
| Calibration: | Certified gas of O_2 balance N_2 approximating 80% of range of analysis or one range higher |
| Compensation: | Temperature |
| Connections: | 1/8" compression tube fittings |
| Controls: | Water resistant keypad; menu driven range selection, cali- bration and system functions |
| Display: | Graphical LCD 2.75 x 1.375"; resolution .01 PPM on 0-10 PPM range |
| Enclosure: | Painted aluminum NEMA 4X, 8.6 x 9 x 3", 12 lbs. |
| Flow Sensitivity: | None between 0.5-5 SCFH, 2 SCFH recommended |
| LED Indicators: | LOW BATT (72 hr. warning); CHARGE mode |
| Linearity: | > .995 over all ranges |
| Pressure: | Inlet - regulate to 5-30 psig; vent - atmospheric |
| Power: | Rechargeable battery, 60 day duty cycle (pump 8 hours) |
| Recovery Time: | 60 seconds in air to < 10 PPM in < 1 hour on $N_{\rm 2}$ purge |
| Response Time: | 90% of final FS reading in 10 seconds |
| Sample System: | None |
| Sensitivity: | < 1% of FS range |
| Sensor Model: | GPR-12-333 |
| Sensor Life: | 24 months at 25°C, 1 atm with average O_2 < 1,000 PPM |
| Signal Output: | 0-1V FS |
| Temp. Range: | 5° to 45°C (GPR sensor), -20° to 45°C (XLT sensor) |
| Warranty: | 12 months analyzer; 12 months sensor |
| Wetted Parts: | Stainless steel |



GPR-1100 GP Portable PPM O₂ Analyzer

Battery Powered PPM Oxygen Analyzer

ISO 9001:2008 QA System INTERTEK Certificate No. 485



| Advanced Sensor Technology |
|--------------------------------------|
| Recovers from Air to 10 PPM < 1 Hour |
| Sensitivity 0.05 PPM (50 PPB) |
| 24 Month Expected Life |
| Excellent Compatibility with CO2 |
| No Maintenance |
| Stainless Steel Wetted Parts |
| Designed for Industrial Use |
| |

Optional Equipment

XLT-12-333 sensor for analysis of a gas mixture with > 0.5% CO₂

PI-2166-4 Integral sampling pump

CC-1030 Carrying case with custom foam insert

Sample conditioning accessories - contact factory

* Subject to change without notice.